

Miracle®

Future Business LLC.



Part# LT118A Miracle 10" LCD Monitor

LD118A Beige	MIRACLE 10.4" LCD XGA 1024 x 768
LCD Display	10.4" TFT LCD, Anti-glare, Hard coating (3H)
Signal input	Video: RGB Analog; Sync.: TTL
Response Time	40ms
Dot Pitch	0.2055 (H) x 0.2055 (V) mm
Resolution	VGA 640 x 480 (60/72/75); SVGA 800 x 600 (56/60/72/75); XGA 1024 x 768 (43/60/72/75)
Contrast Ratio	300 : 1 (typical)
Brightness	150 cd/m ² (typical)
Display color	262K colors
Viewing Angle	L/R: +80°~ -80° (typical); U/D: +80°~ -80° (typical)
Display Size	210.4(H)mm x 157.8(V)mm
Speaker	0.7W per channel
Power Source	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V/2.0A
Power Consumption	<20W
EPA VESA	On, Off, Suspend, Stand by
User Controls	Power on/off with LED, OSD Menu/Select, Adjustment +/-
Input Connector	15 pin D-type signal cable
Operating Temperature	5°C ~ 40°C
Operating Humidity	5% ~ 90%
Dimension	11"W x 5"D x 11"H (without base 11" W x 2" D x 9"H)
Weight	6 lbs (3 lbs without stand)
Wall mount	VESA standard 75 x 75 mm
Certification	FCC, UL, cUL, CCC