

**Miracle<sup>®</sup>**

**Future Business LLC.**



**Part# LT08W Miracle 8" LCD Monitor**

<b>LT08W White</b>	<b>MIRACLE 8.0" LCD SVGA 800 x 600</b>
<b>LCD Display</b>	8.0" TFT LCD, Active Matrix Panel
<b>Signal input</b>	Video: RGB Analog 0.7V (Peak to Peak); Sync.: TTL (Positive or Negative)
<b>Response Time</b>	25ms
<b>Dot Pitch</b>	0.2025 (H) x 0.2025 (V) mm
<b>Resolution</b>	VGA 720 x 400 (70); 640 x 480 (60/72/); SVGA 800 x 600 (60/72/75);
<b>Contrast Ratio</b>	500 : 1
<b>Brightness</b>	250 cd/m <sup>2</sup> ; Twin CCFLs, Long life backlight (MTBF 50000hrs)
<b>Display color</b>	16M colors
<b>Viewing Angle</b>	L/R: +70°~ -70° U/D: +50°~ -60°
<b>Display Size</b>	162(H)mm x 121.5(V)mm
<b>Power Source</b>	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V/1.5A
<b>Power Consumption</b>	<16W;
<b>EPA VESA</b>	On, Off, Suspend, Stand by
<b>User Controls</b>	Power on/off with LED, OSD Menu/Select, Auto/Select, Adjustment +/-
<b>Input Connector</b>	15 pin D-type signal cable
<b>Operating Temp./Humidity</b>	5°C ~ 40°C / 20% ~ 80% (no condensation); Altitude to 10,000 feet
<b>Storage Temp./Humidity</b>	-20°C ~ 60°C / 10% ~ 90% (no condensation)
<b>Dimension</b>	8¼"W x 5"D x 8"H (without base 8¼" W x 1½" D x 6¾" H)
<b>Weight</b>	Net 2.6 lbs (4 lbs with packing)
<b>Wall mount</b>	VESA standard 75 x 75 mm
<b>Certification</b>	FCC, CCC
<b>Touch screen</b>	Option