

Miracle[®]

Future Business LLC.



Part# LT10B Miracle 10" LCD Monitor

LT10B Black

MIRACLE 10.4" LCD SVGA 800 x 600

LCD Display	10.4" TFT LCD, Active Matrix Panel
Signal input	Video: RGB Analog 0.7V (Peak to Peak); Sync.: TTL (Positive or Negative)
Response Time	25ms
Dot Pitch	0.264 (H) x 0.264 (V) mm
Resolution	VGA 640 x 350 (70); 720 x 400 (70); 640 x 480 (60/72/75); SVGA 800 x 600 (56/60/72/75);
Contrast Ratio	300 : 1
Brightness	350 cd/m ²
Display color	262K colors
Viewing Angle	L/R: +60° ~ -60° U/D: +40° ~ -40°
Display Size	211(H)mm x 158(V)mm
Speaker	0.7W per channel
Power Source	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V/2.0A
Power Consumption	16W; standby <5W
EPA VESA	On, Off, Suspend, Stand by
User Controls	Power on/off with LED, OSD Menu/Select, Auto/Select, Adjustment +/-
Input Connector	15 pin D-type signal cable
Operating Temp./Humidity	5°C ~ 40°C / 20% ~ 80% (no condensation); Altitude to 10,000 feet
Storage Temp./Humidity	-20°C ~ 60°C / 10% ~ 90% (no condensation)
Dimension	11"W x 5"D x 11"H (without base 11"W x 2"D x 9"H)
Weight	5.6 lbs (3 lbs without stand)
Wall mount	VESA standard 75 x 75 mm
Certification	FCC, CCC
Touch screen	Option