



**Part# LT15BV Miracle 15" VGA/Video Monitor**

**Features:**

- 15" TFT LCD
- Input: DB15 (VGA), Video, 2 BNC, 2 Audio
- Small base + Wall mountable, buttons on side
- A+ panel, fire resistant material cases

Specifications	
<b>LCD Display</b>	15" TFT LCD Panel
<b>Display Size</b>	304 (H)x228(v)mm
<b>Pixel Pitch</b>	0.297 (H)x0.29(V)mm
<b>Display Mode</b>	VGA 720x400(70Hz) VGA 640x480(60/72/75 Hz) SGVA 800x600(60/72/75 Hz) XGA 1024x768(60/72/75 Hz)
<b>Max Resolution</b>	XGA 1024x768
<b>Display Color</b>	16M
<b>Contrast Rate</b>	350:1
<b>Brightness</b>	250 Cd/m <sup>2</sup>
<b>Response Time</b>	8ms
<b>View Angle(CR&gt;10)</b>	+70 ~ -60° (U/D) +75 ~ -75°(L/R)
<b>Input Signal</b>	R.G.B.Analog 0.7V
	<b>Video Sync</b>
<b>Signal Connector</b>	TTL Positive or Negative
<b>Front Control</b>	DB15, Video, 2 BNC, 2 Audio
<b>OSD</b>	Power,Menu,Auto,Up/+,Down/- "Volume" menu,"Bright-Contrast"menu,"Color"menu, "Image Config"menu, "OSD Menu","Language" menu
<b>Plug &amp; Play</b>	DDC1/2B
<b>Audio System(optional)</b>	1W/Per Channel
<b>Power Adapter</b>	Input AC 100-240V,50-60Hz, Output DC 12V/4.0A
<b>Operating Conditions</b>	<b>Temperature</b> 5° C~35° C (41° F~95 °F)
	<b>Humidity</b> 20%~80%
<b>Storage Conditions</b>	<b>Temperature</b> -20° C ~ 60° C
	<b>Humidity</b> 10% ~90%
<b>Dimensions (WxHxD)</b>	370x350x162mm
<b>Weight (Net)</b>	2.6 Kg
<b>Regulations</b>	FCC, CE

Specifications are subject to change without notice.



back



Connectors



Buttons on side

**Options:**

10" 12" 19" VGA/Video Monitors