

Miracle[®]

Future Business LLC.



Part# LT15H-RU,-RS, Miracle 15" 5 Wire Resistive Touch Monitor

LT15H-RU, -RS	MIRACLE 15" 5 Wire Resistive Touch LCD
LCD Display	15" TFT LCD Panel
Signal input	Video: R.G.B. Analog 0.7V; Sync.: TTL positive or negative
Display Mode	VGA 720x400 (70Hz); 640x480 (60/72/75Hz); SVGA 800x600 (60/72/75Hz); XGA 1024x768 (60/72/75Hz)
Dot Pitch	0.297 (H) x 0.297 (V) mm
Max. Resolution	XGA 1024 x 768
Contrast Ratio	450 : 1 (typical)
Brightness	250 cd/m ² ; (typical)
Display color	16M
Viewing Angle	L/R: +60° ~ -60°(typical); U/D: +40° ~ -60°(typical)
Response	16ms
Speaker	Stereo 0.7W x 2
Power Source	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V
Power Consumption	<30W
Front Controls	Auto, Power, Menu, Up/+, Down/-
Input Connector	15 pin D-type signal cable
Wall Mount	VESA 100 x 100
Operating Temperature,Humidity	0°C ~ 40°C, 20% ~ 80%
Storage Temperature,Humidity	-20°C ~ 60°C, 10% ~ 90%
Dimension	14 ³ / ₄ "W x 14"H x 7 ¹ / ₂ " D
Weight	9 lbs (12 lbs with packing)
Certification	FCC, CE, CCC,