



Future Business LLC.



Part# LT17H-EU Miracle 17" 5 Wire Resistive Touch Monitor

LT17H-EU (Elo)	MIRACLE 17" 5 Wire Resistive Touch LCD
LCD Display	17" TFT LCD Panel
Signal input	Video: R.G.B. Analog 0.7V; Sync.: TTL positive or negative
Display Mode	VGA 720x400(70Hz); 640x480(60/72/75Hz); SVGA 800x600(60/72/75Hz); XGA 1024x768(60/72/75Hz); SXGA 1280x1024(60/72/75Hz)
Dot Pitch	0.264 (H) x 0.264 (V) mm
Max. Resolution	XGA 1280 x 1024
Contrast Ratio	700 : 1 (typical)
Brightness	300 cd/m ² ; (typical)
Display color	16M
Viewing Angle	L/R: +75° ~ -75°(typical); U/D: +75° ~ -60°(typical)
Response	8ms
Touchscreen	Elo driver compatible, USB port
Speaker	Stereo 0.7W x 2
Power Source	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V
Power Consumption	<30W
Front Controls	Auto, Power, Menu, Up/+, Down/-
Input Connector	15 pin D-type signal cable
Wall Mount	VESA 75 x 75
Operating Temperature, Humidity	0°C ~ 40°C, 20% ~ 80%
Storage Temperature, Humidity	-20°C ~ 60°C, 10% ~ 90%
Dimension	15¼"W x 15¾"H x 7½" D
Weight	11 lbs (14 lbs with packing)
Certification	FCC, CE, CCC,