

**Miracle<sup>®</sup>**

**Future Business LLC.**



**Part# LT17H-RU, -RS Miracle 17" 5 Wire Resistive Touch Monitor**

**LT17H-RU, -RS**

**MIRACLE 17" 5 Wire Resistive Touch LCD**

<b>LCD Display</b>	17" TFT LCD Panel
<b>Signal input</b>	Video: R.G.B. Analog 0.7V; Sync.: TTL positive or negative
<b>Display Mode</b>	VGA 720x400(70Hz); 640x480(60/72/75Hz); SVGA 800x600(60/72/75Hz); XGA 1024x768(60/72/75Hz); SXGA 1280x1024(60/72/75Hz)
<b>Dot Pitch</b>	0.264 (H) x 0.264 (V) mm
<b>Max. Resolution</b>	XGA 1280 x 1024
<b>Contrast Ratio</b>	700 : 1 (typical)
<b>Brightness</b>	300 cd/m <sup>2</sup> ; (typical)
<b>Display color</b>	16M
<b>Viewing Angle</b>	L/R: +75° ~ -75°(typical); U/D: +75° ~ -60°(typical)
<b>Response</b>	8ms
<b>Speaker</b>	Stereo 0.7W x 2
<b>Power Source</b>	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V
<b>Power Consumption</b>	<30W
<b>Front Controls</b>	Auto, Power, Menu, Up/+, Down/-
<b>Input Connector</b>	15 pin D-type signal cable
<b>Wall Mount</b>	VESA 75 x 75
<b>Operating Temperature, Humidity</b>	0°C ~ 40°C, 20% ~ 80%
<b>Storage Temperature, Humidity</b>	-20°C ~ 60°C, 10% ~ 90%
<b>Dimension</b>	15¼"W x 15¾"H x 7½" D
<b>Weight</b>	11 lbs (14 lbs with packing)
<b>Certification</b>	FCC, CE, CCC,