



Part# LTS12BV Miracle 12" LCD Monitor

LTS12BV Black	SYSONIC 12.1" LCD SVGA 800 x 600
<b>LCD Display</b>	12.1" TFT LCD, Active Matrix Panel
<b>Signal input</b>	Video: RGB Analog 0.7V (Peak to Peak); Sync.: TTL (Positive or Negative)
<b>Response Time</b>	25ms
<b>Dot Pitch</b>	0.297 (H) x 0.297 (V) mm
<b>Resolution</b>	VGA 720 x 400(70); 640 x 480(60/72/75); 800 x 600(60/72/75)
<b>Contrast Ratio</b>	250 : 1
<b>Brightness</b>	250 cd/m <sup>2</sup>
<b>Display color</b>	262K colors
<b>Viewing Angle</b>	L/R: +50° ~ -50° U/D: +30° ~ -30°
<b>Display Size</b>	245(H)mm x 185(V)mm
<b>Speaker</b>	0.7W per channel
<b>Power Source</b>	AC: 100 ~ 240V, 50 ~ 60Hz; Output: DC 12V/2.0A
<b>Power Consumption</b>	16W; stand by <5W
<b>EPA VESA</b>	On, Off, Suspend, Stand by
<b>User Controls</b>	Power on/off with LED, OSD Menu/Select, Auto/Select, Adjustment +/-
<b>Video Input</b>	Video/Audio in, S-Video in
<b>Input Connector</b>	15 pin D-type signal cable
<b>Operating Temp./Humidity</b>	5° ~ 40° / 20% ~ 80% (no condensation); Altitude to 10,000 feet
<b>Storage Temp./Humidity</b>	-20° ~ 60° / 10% ~ 90% (no condensation)
<b>Dimension</b>	12¾"W x 6"D x 12¼"H (without base 12¾" W x 2" D x 10¾" H)
<b>Weight</b>	6.8 lbs (4 lbs without stand)
<b>Wall mount</b>	VESA standard 100 x 100 mm
<b>Certification</b>	FCC, CCC
<b>Touch screen</b>	Option